

NEW Salad Sandwich Prep Tables

■ EDST27-8-B

■ EDST-60-16-B

■ EDST48-12-B

□ EDST-72-18-B

STANDARD FEATURES

¥ DURABLE STAINLESS STEEL

Our prep tables boast a sturdy stainless steel exterior and interior finish. Galvanized back panel provides strength and durability.

₩ ERGONOMICALLY DESIGNED SOLID DOORS

Standard doors come with easy grip handles and self closing/120 ° stay open door feature, working together for customer convenience while ABS door liner provides thermal efficiency.

¥ MAGNETIC DOOR GASKET

One piece magnetic gasket is removable without tools for ease of cleaning and replacement. Door's in step design gives added protection to the gasket.

₩ EFFICIENT REFRIGERATION SYSTEM

Factory engineered oversized and balanced refrigeration system. CFC-free R-134A refrigerators maintain temperature from 33° to 38°F. Forced air design underneath pans to keep products fresh.

₩ FRONT BREATHING

Allows unrestricted placement of the unit.

₩ HIGH DENSITY POLYURETHANE INSULATION

Ecomate® 2" CFC-free polyurethane insulation foamed in place for extra strength and energy efficiency. Environmentally friendly with zero ozone depletion potential (ODP) and zero global warming potential (GWP).

₩ INSULATED LIDS

Removable insulated lids keep food fresh and cold by reducing condensation.

₩ REVERSIBLE & EASY CLEAN CUTTING BOARD

The full length removable white polyethylene cutting board provides a comfortable 10" of work space.

₩ STANDARD WITH FULL SETS OF 1/6th PANS, 4" DEEP

* Except for the EST27-B: two of the pans are 1/9th size. It can also accommodate 6" deep pans.

ACCESSORIES

Additional epoxy coated shelves
















MODEL	DOORS	TOP PANS	SHLVS.	AMPS	НР	VOLTAGE	NEMA PLUG	CORD LENGTH	CABINE W	T DIMEN	SIONS H**		PING Cubes
REFRIGERATOR													
EDST27-8-B	1	8	1	2.7	1/6	115/60/1	5-15P	8'	27"	30"	37"	214	33
EDST48-12-B	2	12	2	5.4	1/4	115/60/1	5-15P	8'	48"	30"	37"	305	55
EDST60-16-B	2	16	2	6.7	1/3	115/60/1	5-15P	8'	60"	30"	37"	370	68
EDST72-18-B	3	18	3	6.7	1/3	115/60/1	5-15P	8'	72"	30"	37"	455	81

 $^{^{*}}$ Depth does not include 1" rear bumper ** Height does not include 5" overall for casters







EDST27-8-B Top




EDST48-12-B Top




EDST60-16-BTop




EDST72-18-B Top



EDST27-8-B Front



EDST48-12-B Front




EDST60-16-B Front



EDST72-18-B Front



EDST Common View













Specifications

- EXTERIOR: Stainless steel, galvanized steel back.
- INTERIOR: Stainless steel.
- CABINET & DOOR: Entire foamed-in-place highdensity, CFC-free, polyurethane insulation. Coved corner floor to meet ETL requirements.
- Casters: 4" Diameter swivel casters, front two with brakes.

④ DOORS

- Stainless steel exterior with ABS interior liner.
- One piece magnetic gasket is removable without tools for easy cleaning.
- Self-closing doors with 120° stay open feature and recessed handles for convenient loading and unloading.

REFRIGERATION SYSTEM

- Oversized and balanced refrigeration system.
- R-134 A holding temperature at 33°F to 41°F refrigerators
- Self-contained capillary tube system uses environtmentallyfriendly and CFC-free refrigerant.
- Front breathing allows unrestricted placement of the unit.
- Evaporator coil is mounted in the rear of the unit with full accessibility from the back.
- Large fan motor and fan blades for better air circulation.
- Self contained system, no plumbing nesessary.
- Access for the condensing unit behind the front grill, slides out for easy cleaning and maintenance.

④ ELECTRICAL

 The whole unit is completely pre-wired at factory with cord and plug set included and ready for final connection to a 115/60/1 phase.

4 WARRANTY

Continental US & Canada:

- One year labor and parts warranty.
- Five year compressor warranty.
- International: one year parts only.